



CONDUIT ID RANGE	APPLICABLE 5" [125mm] CONDUIT	PORT RANGE
4.95" - 5.15" [125.73mm - 130.81mm]	PVC SCH 40 HDPE SCH 40 F2160	1.28" - 1.32" [32.51mm - 33.52mm]

Applicable conduit types based on product's conduit ID range meeting or exceeding conduit ID dimensions specified in one or more of following standards: UL651, UL651A, ASTM F2160, NEMA TC 6 & 8



- NOTES:
- 1 Material: PVC
 - 2 Material: TPE
 - 3 Material: Stainless Steel
 - 4 Material: Vinyl

TITLE		TRIPLEX ENTRY SEAL, 5.00" 125mm, PORT 1.30" 33mm			
PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF CAL AM MANUFACTURING. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF CAL AM MANUFACTURING IS PROHIBITED.	DRAWN	JC. MORENO	DATE :	06/24/2025	
	DRAWING NO.	7350-130	UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCES: X±0.1 X.X±0.05 X.XX±0.030 X.XXX±0.020		
	REVISION	B			
	SCALE:	1:3	PRODUCT NUMBER:	7350-130	
				SHEET 1 OF 1	